

## XL 275c2



### Specifications:

Channels	no	<b>2</b>
Class	Typ	<b>AB Full Mosfet</b>
Power @14,4V /1.0% THD		
@ 4 ohm stereo:	Wrms	<b>2x 285</b>
@ 2 ohm stereo:	Wrms	<b>2x 470</b>
@ 4 ohm mono:	Wrms	<b>1x 940</b>
@ 2 ohm mono:	Wrms	<b>1x 1500</b>
Operation supply	V	<b>10 -16</b>
Thermal protection	C	<b>80</b>
THD @ 4 Ω / 50% Pmax	%	<b>0,05</b>
Signal/noise	dB	<b>90</b>
Band width +- 1 dB	Hz	<b>13 -36000</b>
Input sensitivity	Vrms	<b>0,2-8</b>
Low input impedance	Ω	<b>10 k</b>
High input impedance	Ω	<b>33</b>
Damping @ 80 Hz		<b>455</b>
Power consumption, idle	A	<b>1.5</b>
Power cons. 4 Ω stereo	A	<b>45</b>
Power cons. 4 Ω mono	A	<b>92</b>
Power cons. 2 Ω mono	A	<b>176</b>
Weight	kg	<b>5,7</b>
Dimensions	l/w/h	<b>546/180/58 mm</b>

### Features:

- Input with low- or high-level signal, RCA output
- High-level with autosense function (no remote signal required)
- Variable switchable Low Pass Filter from 50 to 300 Hz
- Variable switchable High Pass Filter from 25 to 175 Hz
- 12 dB octave crossover slope
- Bass adjust +/- 6 dB (car- resp. woofer-size)
- Optional remote available

### Miscellaneous:

- Protection for overhead, over current, short circuitry and speaker DC protection
- Massive heavy aluminum-heat sink with intelligent fan cooling